

SYSTEM DATASHEET

Ceiling cladding OSF - 2x12,5 GKB A + GKF DF/KAP

on a hat profile structure, hybrid with double sheathing with GKB type A boards, thickness 12.5 mm and type DF with a thickness of 12.5 mm



Ceiling cladding elements

1. Norgips S GKB type A plasterboards of 12.5 mm thickness 12.5 mm
2. Norgips S GKF type DF gypsum plasterboard , thickness: 12.5 mm
3. Norgips top hat profiles, max. axial spacing every 40 cm
4. Optional Norgips sealing tape, width 30 mm
5. Norgips 3.5 x 25 mm sheet metal screws, max. spacing every 40 cm
6. Norgips 3.5 x 35 mm sheet metal screws, max. spacing every 17 cm
7. Steel dowels, min. \varnothing 6 x 40 mm in two rows every 100 cm
8. Norgips Start & Finish ready-made joint compound or Norgips Start gypsum joint compound
9. Norgips reinforcing tape
10. Ready-made joint compound Norgips Extra Finish, ready-made joint compound Norgips Start & Finish, gypsum joint compound Norgips Finish

Technical data



Fire resistance class
EI 30 ¹⁾



Wall mass
22 kg/m²



Cladding mass
24 kg/m²

The above-mentioned parameters apply to a partition made of sheet metal profiles with a thickness of 0.55 and 0.6 mm.

¹⁾ Based on classification no. LBO-1587-K/22

Standard

☆☆☆ SUPER

It provides a very stable building with the highest fire resistance, sound insulation and hardness.



