

# ANGLE BRACKET 44

Angle bracket for door frame profiles UA50

**NORGIPS®**



## PRODUCT DESCRIPTION

Angle bracket made of zinc-coated 2.0 mm steel sheet and width 44 mm.

## INTENDED USE

Designated for fastening door frame profiles when making doorways in partition or façade walls. The angle bracket is affixed to the profile with M8 bolts and to the floor with mechanical fasteners. Suitable for indoor plasterboard lining.

## TECHNICAL PARAMETERS

Material	DX51D
Sheet metal gauge [mm]	2,0
Zinc-coating	Z140
Atmospheric corrosivity category	C1, C2
Tensile strength [N/mm <sup>2</sup> ]	270 do 500
Reaction-to-fire performance	A1



Plasterboards + Profiles + Compound + **Accessories** = NORGIPS Solution

**ADVANTAGES**

- **Modularity.** Tested as a part of NORGIPS plasterboard lining systems.
- **Fire safety.** Tested as a part of fire protection systems with declared fire resistance rating.
- **Marking.** Designations for easy product identification.

**DIMENSIONS AND PACKAGING**

Bulk packaging	Number of units in a packaging [pcs]
Cardboard box	48

**NOTES FOR GUIDANCE**

Use the angle brackets in accordance with manufacturer’s recommendations and design guidelines.

Consult any other area of application with the design engineer.

**ADDITIONAL INFORMATION**

Applicable standard: PN-EN 14195: 2015 Metal framing components for gypsum board systems – Definitions, requirements and test methods.

Declaration of Performance: available on the website [www.norgips.pl](http://www.norgips.pl)

**NORGIPS sp. z o.o.**

ul. Krakowiaków 50,  
02-255 Warsaw, PL  
tel. + 48 605 338 181

[www.norgips.eu](http://www.norgips.eu)

The data presented in this leaflet constitutes solely a product description. It represents a general guidance based on our knowledge and experience, not related to specific applications. Since our products are subjected to constant improvements and development, we reserve the

right to change their parameters without prior notice. The data presented herein cannot form a basis for any claims. If you have any questions, please contact the Norgips Technical Department / Norgips Representative.