

NORGIPS START & FINISH

NORGIPS®

Ready-mixed dual-purpose filler and finishing compound for grouting plasterboard joints and full-surface levelling of mineral substrates



PRODUCT DESCRIPTION

- Grouting of plasterboard joints strengthened with reinforcing tape (Q1)
- Finishing grouting of plasterboard joints (Q2)
- Full surface thin-layer levelling of plasterboard surfaces (Q3,Q4)
- Full-surface thin-layer levelling of mineral substrates
- Scratch and chip filling on mineral substrates
- Embedding corner beads in dry lining systems
- Levelling of visible mounting and finishing elements
- Levelling of low-adhesion surfaces



ADVANTAGES

- All-purpose product suitable for any quality level of plasterboard joint grouting and surface levelling (Q1, Q2, Q3, Q4).
- Replaces both jointing and finishing compounds
- Suitable as finishing compound for fire-rated partitions (Q2, Q3,Q4)
- Excellent adhesion
- Suitable for increased humidity environments (bathrooms, kitchens)
- High resistance to cracking
- Suitable for mechanical application

TECHNICAL PARAMETERS

| | |
|------------------------------|---|
| Type | 3A compliant with EN 13963:2005 AC 2006 |
| Reaction-to-fire performance | A2-s1, d0 – completely non-combustible |
| Permissible thickness | 0-3 mm for one-layer application |
| Temperature of application | Min. 10°C |
| Consumption | 0,15 kg/m ² – grouting of Norgips plasterboard joints with use of reinforcing tape (Q1) 0,10 kg/m ² – finishing grouting of Norgips plasterboard joints (Q2) 1,1 kg/mm/m ² – full-surface levelling (Q3, Q4) |
| Shelf life | 12 months |
| Packaging | Bucket: 3,7 kg (18 or 48 pcs. per pallet), 20 kg (8 or 33 pcs per pallet) |

RELATED PRODUCTS

| Pack. | Designation | Description | Pack. | Designation | Description |
|---|-----------------------------|--------------------------------|---|--------------------------------|--|
|  | NORGIPS EXTRA FINISH | Ready-mixed finishing compound |  | TAŚMA PAPIEROWA NORGIPS | Reinforcing tape for plasterboard joints |



Plasterboards + Profiles + **Compound** + Accessories = NORGIPS Solution

DIMENSIONS AND PACKAGING

| Packaging (kg) | Quantity per pallet | |
|-------------------|---------------------|-------|
| | (pcs) | (kg) |
| 3,7 | 18 | 66,6 |
| 3,7 | 48 | 177,6 |
| 20 | 8 | 160 |
| 20 | 33 | 660 |

SUBSTRATE PREPARATION

The substrate should be dry and in sound condition and free of grease, dirt, dust and loose particles. Prior to the compound application, low-adhesion substrates (e.g., oil paints) should be sanded dull, e.g., with sandpaper, and then cleaned of dust and loose particles. Absorbent or unstable substrates should be reinforced with a deep penetration primer.

PRIMER PREPARATION

Before laying on the compound, gently mix it manually or with a low-speed mixer. In the case of mechanical application, the compound can be slightly thinned by adding clean water in portions not greater than 250 ml, until reaching the required consistence. Mix the compound after adding water. Use clean tools for the application.

COMPOUND APPLICATION

The compound can be laid on manually or mechanically. The maximum compound thickness laid on in one layer may not exceed 3 mm.

ADDITIONAL INFORMATION

- Use the compound at air and substrate temperatures of at least +10°C. Store in a closed packaging at +1°C to +35°C without exposing the product to freezing or sunlight. After short-term freezing, unfreeze the product at room temperature.
- The compound drying time depends on the room temperature and humidity (it takes usually up to 12 hours).
- The shelf life is 12 months.
- For more information, please refer to www.norgips.pl

NORGIPS sp. z o.o.

ul. Krakowiaków 50,
02-255 Warsaw, PL
tel. + 48 605 338 181

www.norgips.eu

The data presented in this leaflet constitutes solely a product description. It represents a general guidance based on our knowledge and experience, not related to specific applications. Since our products are subjected to constant improvements and development, we reserve the

right to change their parameters without prior notice. The data presented herein cannot form a basis for any claims. If you have any questions, please contact the Norgips Technical Department / Norgips Representative.