

ALL-PURPOSE FLEX PROFILE

NORGIPS®

All-purpose profile



PRODUCT DESCRIPTION

All-purpose profile made of zinc-coated 0.6 mm sheet metal. Available in 125 mm width.

INTENDED USE

This profile is designated for inner and outer corners of attic linings with the aim to eliminate potential cracks and scratches. Intended for indoor use. Facilitates execution of decorative ceilings, multi-level suspended ceilings, ceiling linings and installation of LED lighting. Thanks to its double-row perforation, facilitates bending the tape.

TECHNICAL PARAMETERS

Material	Zinc-coated sheet metal
Sheet metal gauge [mm]	0.6
Tensile strength [N/mm ²]	Met
Reaction-to-fire performance	A1



Plasterboards + **Profiles** + Compound + Accessories = NORGIPS Solution

ADVANTAGES

- **Elasticity.** Made of sheet metal with two-row perforation.
- **Profile designations.** To facilitate the product identification, designations are placed directly on the profiles.

DIMENSIONS AND PACKAGING

Length (m)	Bulk packaging [pcs]	Unit weight [kg/m]
12	3	0,52

NOTES FOR GUIDANCE

Use the profiles in accordance with manufacturer's recommendations and design guidelines. For all other uses, consult the design engineer.

ADDITIONAL INFORMATION

Applicable standard: PN-EN 14353: 2017 Metal beads and feature profiles for use with gypsum plasterboards – Definitions, requirements and test methods.

Declaration of Performance: available on the website www.norgips.pl

NORGIPS sp. z o.o.

ul. Krakowiaków 50,
02-255 Warsaw, PL
tel. + 48 605 338 181

www.norgips.eu

The data presented in this leaflet constitutes solely a product description. It represents a general guidance based on our knowledge and experience, not related to specific applications. Since our products are subjected to constant improvements and development, we reserve the

right to change their parameters without prior notice. The data presented herein cannot form a basis for any claims. If you have any questions, please contact the Norgips Technical Department / Norgips Representative.